Customized 30mm Stainless Steel Welded Tube 3.5 Inch 4 Inch 5 Inch

Basic Information

Place of Origin: china
Brand Name: ShengQuan
Certification: ISO9001:2000

Model Number: 201/304/304L/316/316L/321/309/310/32750/32760/90

• Minimum Order Quantity: 1tor

• Price: USD1500-USD6000

Packaging Details: Standard Export Sea-Worthy Packing

• Delivery Time: 5-15days

Payment Terms:
 L/C, T/T, Western Union

Supply Ability: 15000Tons



Product Specification

Application: Construction, Kitchenware, Decoration, chemical construction, Constr

• Width: Or As Required

• Type: Plate, Coil, stainless Steel Sheet

Standard: ASTM,JIS,AISI,EN,GBLength: Customer's Request

• Grade: 201/202/304

/304L/316/316L321/310s/410/420/430/440/43

Product Name: ASTM JIS SUS 201 202 301 304 304I 316

316l 310Stainless Steel Sheet

• Thickness: 0.3mm-120mm,0.18-1.5mm,0.2-60mm,0.45-

5mm,0.01-200mm

• Certification: ISO,SGS,Other

• Technique: Cold Rolled Hot Rolled

• Highlight: 30mm stainless steel welded tube,

5Inch stainless steel welded tube, Customized 30mm stainless steel tube



316LN X2CrNiMoN17-11-2 1.4406 Seamless Stainless Steel Tubing 3.5 Inch 4 Inch 5 Inch

Stainless steel pipe resists oxidation, making it a low-maintenance solution that is suitable for high temperature and chemical applications. Because it is easily cleaned and sanitized, stainless steel pipe is also desired for applications involving food, beverages, and pharmaceutical applications.

Stainless steel pipe is primarily used in piping systems for the transport of fluids or gases. We manufacture steel pipe from a steel alloy containing nickel as well as chromium, which give stainless steel its corrosion-resistant properties. Stainless steel pipe resists oxidation, making it a low-maintenance solution that is suitable for high temperature and chemical applications. Because it is easily cleaned and sanitized, stainless steel pipe is also desired for applications involving food, beverages, and pharmaceutical applications.

| | l | L | l _ | | | L., | ۱ | Si | l <u>.</u> | L | Мо |
|-------------|------|------------|-------------------|---------------|--------------|------------|-----------|-----------|----------------|---------------|-------------|
| | ASTM | EN | JIS | C% | Mn% | P% | S% | % | Cr% | Ni% | % |
| S201 00 | 201 | 1.437 2 | SUS20 1 | ≤0.15 | 5.5- 7.5 | ≤0.0 6 | | ≤1. 00 | 16.0- 18.0 | 3.5- 5.5 | - |
| S202 00 | 202 | | SUS20 | ≤0.15 | 7.5- 10.0 | ≤0.0 6 | | ≤1. 00 | 17.0- 19.0 | 4.0- 6.0 | - |
| S301 00 | 301 | I | SUS30 1 | ≤0.15 | ≤2.00 | | ≤0. | ≤1. 00 | 16.0- 18.0 | 6.0- 8.0 | - |
| S304 00 | 304 | 1.430 1 | SUS30 4 | ≤0.08 | ≤2.00 | | ≤0. | ≤0. | 18.0- 20.0 | 8.0- 10.5 | - |
| S304 03 | 304L | 6 | SUS30 4L | ≤0.03 | ≤2.00 | ≤0.0 45 | ≤0. 03 | ≤0. 75 | 18.0- 20.0 | 8.0- 12.0 | - |
| S309 08 | 309S | 1.483 3 | SUS30 9S | ≤0.08 | ≤2.00 | ≤0.0 45 | | l | 22.0- 24.0 | 12.0- 15.0 | - |
| S310 08 | 310S | 5 | SUS31 0S | ≤0.08 | ≤2.00 | | 03 | | 24.0- 26.0 | 19.0- 22.0 | - |
| S316 00 | 316 | 1.440 1 | SUS31 6 | ≤0.08 | ≤2.00 | ≤0.0 45 | | ≤0. 75 | 16.0- 18.0 | 10.0- 14.0 | 2.0- 3.0 |
| S316 03 | 316L | 4 | SUS31 6L | ≤0.03 | ≤2.00 | 45 | 03 | ≤0. 75 | 16.0- 18.0 | 10.0- 14.0 | 2.0- 3.0 |
| S317 03 | 317L | 8 | SUS31 7L | ≤0.03 | ≤2.00 | | 03 | | 18.0- 20.0 | 11.0- 15.0 | 3.0- 4.0 |
| S321 00 | 321 | 1 | SUS32 1 | <u>≤</u> 0.08 | ≤2.00 | | 03 | 75 | 17.0- 19.0 | 9.0- 12.0 | - |
| S347 00 | 347 | 1.455 0 | SUS34 7 | ≤0.08 | ≤2.00 | ≤0.0 45 | ≤0. 03 | ≤0. 75 | 17.0- 19.0 | 9.0- 13.0 | - |
| S405 00 | 405 | 2 | SUS40 5 | ≤0.08 | ≤1.00 | l . | 03 | ≤1. 00 | 11.5- 14.5 | ≤0.60 | - |
| S409 00 | 409 | 2 | SUS40 9 | ≤0.08 | ≤1.00 | | 03 | ≤1. 00 | 10.5- 11.75 | ≤0.50 | - |
| S430 00 | 430 | 6 | SUS43 0 | ı | ≤1.00 | шп | กร | ≤0. 75 | 16.0- 18.0 | ≤0.60 | - |
| S434 00 | 434 | Γ | 5 SUS43 4 | | | | | | 16.0- 18.0 | - | - |
| S444 00 | 444 | 1 | SUS44 4L | ≤0.025 | | | 03 | ≤1. 00 | 17.5- 19.5 | ≤1.00 | - |
| S403 00 | 403 | - | SUS40 3 | ≤0.15 | 5.5- 7.5 | ≤0.0 4 | 03 | ≤0. 50 | 11.5- 13.0 | ≤0.60 | - |
| S410 000 | 410 | ا م | SUS41 0 | ≤0.15 | ≤1.00 | ≤0.0 35 | 03 | 00 | 11.5- 13.5 | ≤0.60 | ≤1.0 0 |
| S420 00 | 420 | 1.402 1 | 0 SUS42 0J1 | 0.16~0 .25 | ≤1.00 | ≤0.0 4 | | ≤1. 00 | 12.0- 14.0 | ≤0.75 | ≤1.0 0 |

| S440 A | 440A | l | SUS44 0A | 0.60~0 .75 | ≤1.00 | ≤0.0 4 | ≤0. 03 | ≤1. 00 | 16.0- 18.0 | - | ≤0.7 5 |
|------------|-------------|------------|-------------|---------------|-------|------------|-----------|-----------|---------------|---|-------------|
| S327 50 | SAD2 507 | 1.441 0 | | ≤0.03 | ヒロン | ≤0.0 35 | | ı | | | 3.0- 5.0 |
| S318 03 | SAF2 205 | 1.446 2 | | ≤0.03 | ≤2.0 | ≤0.0 3 | l | l | ı | | 2.5- 3.5 |
| N089 04 | 904L | 1.453 9 | | ≤0.0.3 | とり ハ | ≤0.0 35 | l | l | ı | | 3.0- 4.0 |





Packing & Delivery

1. Who are we?

We are based in wuxi, China, start from 2021, sell to Mid East(35.00%), South America(20.00%), Southeast Asia(20.00%), Africa(5.00%), Eastern Asia(5.00%), Northern Europe(5.00%), Southern Europe(5.00%), South Asia(5.00%). There are total about 51-100 people in our office.

2. How can we guarantee quality?

Always a pre-production sample before mass production; Always final Inspection before shipment;

3. What can you buy from us?

steel sheet coil,ppgi ppgl,galvanized steel coil,aluminum steel coil sheet,stainless steel

4. Why should you buy from us not from other suppliers? Integrating the superior resources of China's steel industry, we provide customers with high-quality steel products at preferential prices, and can ensure that the goods are delivered to customers in a timely manner.

5. What services can we provide?

Accepted Delivery Terms: FOB,CFR,CIF,EXW,FCA,DDP,DDU,Express Delivery

Accepted Payment Currency: USD, EUR, CNY;

Accepted Payment Type: T/T,L/C,Credit Card,Weste





15370898866



523639146@gg.com



metalsstainless-steel.com